Technical Specification of Operation Theatre Positioning Devices ³/₄ Length Operation Theatre Table Pad Flat Type (With Cut Out) Standard Green No Film

| | Generic / Technical | Compliance Statement(s) |
|--|--|---|
| Name of Item | Specifications 34 Length Operation Theatre Table Pad Flat Type (With Cut Out) Standard Green No Film | 34 Length Operation Theatre Table Pad Flat Type (With Cut Out) Standard Green No Film |
| Technology/ Product | Specifications | |
| Product Category | As mentioned in catalogue or website: otcare.co.in | 34 Length Operation Theatre Table Pad (s) |
| Purpose of Product | As defined in catalogue | ¾ Length Operation Theatre Table Pads (With Cut Out) provide complete pressure redistribution preventing bed sores, pressure, shear and frictional impact |
| Product Design (with markings) | Product Image with marking of dimensions | Height (H) |
| Material | Medical Grade cured gel which doesn't flow out | Yes |
| Type of Gel Technology | Viscoelastic Gel with Covid Coat+ (Anti-microbial coating) or C3I Gel | C3I Gel |
| Generic Technology Name | C3I Gel (CC+) or C3I Gel | C3I Gel |
| Brand Name or OEM | Whether the item is required with/ without Brand Name i.e. OEM | Without Brand Name: OEM or optional as per buyer |
| Color of Product | Sapphire Blue/ Emerald Green/Custom Color | Green Emerald |
| Type of Construction | Film/ No Film (single continuous phase) | No Film (Single Continuous Phase) |
| Specifications of Iten | | |
| Item Code | As per listed SKU Code | EGR-NF-3/4LOTP-WCO-SD |
| Size of Item, Number of Items Per Pack | Neonatal/ Small/ Medium/ Adolescent/ Large/ Adult/ Extra Large/ Standard Size | Standard (SD), Piece Per Pack |
| Dimensions of Item | As mentioned in catalogue specific to item with definition of each annotation used. | L*W*H (in mm) = 1150 X 500 X 12 mm wherein L = Length; W = Width; H= Height |

| Dimensional marking of item | Grey Image of Product Item with specific marking of each dimension | |
|---|---|--|
| Dimension of Pack (Wooden: Cardboard Box) | Dimension of Wooden: Cardboard Box (Length X Breadth X Height) from exterior side (in cms) | |
| | Hit was Length (L) Height (H) | NA |
| Dimensional Marking of Pack (Wooden: Cardboard Box) | Marking of Exterior Length, Breadth and Height of Wooden: Cardboard Box (in cms) | NA |
| Net weight of Item | Weight of item (in grams) without any accessories or packing | 6200 grams |
| Gross Weight (Item with Wooden: Cardboard Box) | Gross weight inclusive of item, its accessories and Wooden: Cardboard box used for packing (in grams) | 6200 grams |
| Specification (with o | ptional choices) | |
| Pandemic Resilience Ability: Prevent Spread of Infection | Specialized Gel Technological Variant with Covid Coat+ (sustainable solution that is tested against hospital pathogens responsible for Hospital Associated Infections) | No |
| Packaging: Internal Environment assurance and accessories inside pack | Option 1: Viscoelastic Gel with Covid Coat+ (with/ without) film based item should have anti-microbial sticker, air clean pouch and 50 ml of Covid Coat+ solution. Option 2: C3I Gel (with/ without film) doesn't contain any accessory items | No accessory items are provided in the box. |
| Compliance Statement with AST SOPS (Digital Access) (Optional) | Option 1: Compliance Statement (Generic)/ Specific to Product should be provided in physical or digital format ensuring patient safety as per laid down | No such access of such information provided in the pack. |

| | Guidelines by Association of Surgical Technologist(s) SOPs for Positioning Devices Option 2: No such access of information provided with pack | | ک |
|--|---|---|---|
| Barcodes (optiona | Al) Option 1: Bar codes specifying item information should be available outside box. Option 2: No Barcode is provided on the pack. | No barcode specifying company information is provided on the box. | |
| Acceptance Test Procedures Compliance (optional) | Option 1: User Manual provides description of ATPs which minimally suffice testing parameters to establish (a) environmental friendly material; (b) elastomerism; (c) hydrophobicity; (d) cold tolerance; (e) impact resistance and; (f) destructive testing, thereby ensuring the nature of gel technology to support the requirements of operation theatre positioning device Option 2: User Manual is not provided with testing Kit | User Manual is not provided with Testing Kit in this pack. | |
| User/ Technical / Maintenance man to be supplied in English & Hindi in hard and soft Cop | uals Option 1: Bilingual (in physical and digital copy) User Manual with third optional language (digital access) as per specific provision of order only (if | No User Manual is provided with Packaging Kit. | |



Manufacturing Certifications and Product Standards Operation Theatre Positioning Devices

| | Generic / Technical Specifications | Compliance Statement(s) |
|--------------------------------|--|--------------------------------------|
| Product Standard Certification | CE or any other standard (if applicable) Certification Number, | CE Certification Number: CE-97801 |
| | Date | Date: 09-04-2021 to 08-04-2024 |
| Manufacturer's Quality | ISO 9001: 2015 and ISO 13485: | ISO 9001: 2015 |
| Standard | 2016 as well as any other | Cert No : 305021041024Q |
| | standard with its number and date | Date: 10-04-2021 |
| | | ISO 13485: 2016 |
| | | Cert No: MD-9014121 |
| | | Date: 09-04-2021 |
| Certification regarding | REACH standard assuring Gel | REACH |
| chemical inertness | free from any hazardous | Cert No: CH:TX: 1142028342 |
| | /environment degrading constituents | Date: 29-09-2020 |
| | Cert Number & Date | |
| GMP Certification | Standards for Global | WHO: GMP |
| | Manufacturing Practices- Best | Cert No: UQ-901241 |
| | Practices adopted for | Date: 09-03-2021 to 08-03-2024 |
| | development of medical devices | |
| | i.e. WHO: GMP | |
| | Cert No and Date | |
| QCI Certification | Certification issued by Quality | QCI |
| | Council of India (QCI) for | Cert No: VA-452406728758919 |
| | adoption of best quality practices | Date: 27-7-2021 to 26-07-2024 |
| | in development, occupational hygiene, management, safety | |
| | and other aspects. | |
| | | |

Technical Specifications: Material, Technology, Packaging, Purchase & Site Utilities Operation Theatre Positioning Devices

| | Generic / Technical Specifications | Compliance Statement(s) |
|---------------------------|---|---|
| Category | Health Care Device/ Non-Health Care Utility Device/ Both | Health Care Device |
| Toxin Free Composition | Material to be Latex free | Latex, Plasticizer, Phalates, Silicone and |
| | Material to be Phalates free | Polyurethane Free Gel. |
| | Material to be Polyurethane Free | |
| | Plasticizer & silicone free Gel | |
| Human Safe | Material to be non toxic, Skin | Compatible with skin even during long |
| | compatible and inert | duration usage while in direct contact with |
| | | skin during surgeries |
| Eco-friendly and | Material shall be eco-friendly and | Gel material is REACH certified, thus |
| Recyclable | recyclable | environment friendly as well can be recycled. |
| Elasticity of Material | Item is designed to evenly distribute | Elastomeric Cushioning Gel complies with |
| (Elastomeric Cushioning) | the body pressure to prevent | minimum requirement of Elongation strain |
| | circulatory disturbance and pressure | withstands ability (\geq 500%) while |
| | ulcer at the bony prominences | simultaneously Shore A value limits to Zero. |
| Elongation Strain Ability | Elastomeric Ability is estimated as | 543% |
| (%) | elongation strain withstands ability | |
| | with minimum of 500%. | |
| Soft Cushioning | Material having Shore A value limits | Item's material has Shore A value limits to |
| | to zero | Zero indicating its extreme softness |
| | | preventing pressure sore |
| Conforming Ability | Device should be able to complement | Complete: Designed according to body |
| (Complete/ Partial) | body's contours completely | contours to prevent intra operative skin |
| | | injuries and to avoid respiratory or nerve |
| | | injuries |
| Non-Leaky | Material should not flow on prick | Elastomeric Gel is closed cell structure that |
| | | doesn't leak out when pricked or punctured. |
| Density | 0.3 to 0.9 g/cc | Density of material used in development of |
| | "Optimal value attributes towards | item has density of 0.8 g/cc (4.9 lb/foot). |
| | strength of Positioning Device to hold | |
| | body weight while not losing | |
| | flexibility" | |
| Compression Set in | Should be least so that it does not get | 3.3 |

| Material (%) | compressed with time. | |
|--|--|---|
| Repeated Usage : Bottom Out Resistance Ability | Device should be reusable and should not bottom out on repeat usage | Organic, inert & reusable which don't bottom out on repeated usage due to high density with least compression set. |
| Weight bearing capacity of the gel pad/ device (in Kg) | ≥200 Kg | Item is able to hold 200 Kg of patient's weight at vertical angle of placement. |
| Rebounding Capacity | Device should not be immersive and rebound in less than 1 second | Item has high rebounding capacity, on withdrawal of external pressure, in less than fraction of second it rebounds, thereby, preventing pressure due to any bony prominence. |
| Intrinsic Impact Resistant Ability | Impact Resistant ability is linked to its tensile strength with optimal core value of 10 Kg/ cm ³ . | Gel material used in development of item complies with requirement of optimal core value of Tensile strength of 10 Kg/ cm ³ . |
| Tensile Strength of the technology (Kg/ cm ³) | Optimal core value of 10 Kg/cm ³ | 11.4 Kg/ cm ³ |
| Crush Strength | No permanent deformation even after n = 1000 crushing cycles at 1600 psi. | Yes, material complies with such requirement for Crush Strength. |
| Uniform Pressure Distribution | Complete / Partial | Complete pressure re-distribution realized as tear strength ranges from 1.0 -4.5 kN/m and also reduces capillary interface pressure thereby preventing bed sores, pressure, shear and frictional impact during prolonged surgeries |
| Tear Strength (kN/m) | Should be in range of 1-4.5 kN/m | 4.17 |
| Capillary Interface Pressure Reduction Ability | Able to reduce capillary interface pressure to 32 mm Hg or less | Yes, it complied with this requirement. |
| X- Ray Observation Compatibility | Device should be translucent to X- ray. | Item is translucent to X-ray |
| Non-Conductive Material | Device should be non-conductive | Item is non-conductive, an essential property for its utility in magnetic environment as well as doesn't produce static charge. |
| C ARM / MRI Compatible | Device should be compatible for usage in C Arm and MRI | Item is compatible for usage in C ARM and MRI sections of hospital due to its non- conductivity. |
| | | |
| Range of the usage temperature(in ^o Celsius) | 12-40°C | Item is maximally effective in this ambient range of 12-40°C. |

| | freeze or crack under standard | withstand up to 30°C with no areaks | |
|--|--|--|---|
| | operating conditions and withstand | withstand up to -30°C with no cracks. | |
| | upto -30°C during storage / transit | | |
| Non-supportive to microbial growth | Hypoallergenic/ non-toxic & doesn't support any microbial growth | Gel material by its intrinsic composition doesn't support any microbial growth. | L |
| Anti-Microbial Coating | Standard anti-microbial coating is required as per Infection Control Guidelines of Hospital. | Item is coated with anti-microbial coating to prevent growth of opportunistic pathogens | |
| Washability | Positioning Device can easily be cleaned using standard operating room/ hospital based detergents. | Easily cleaned using Standard Hospital Detergents, instruction manual is provided in every pack as well as available digitally with QR code on each pack. | |
| Hot Operation Theatre Compatible | Positioning Device that can be used directly with partially contaminated victim of Chemical and Radiological Emergency for Emergency Surgeries in Hot OTs | Compatible for decontamination procedures to remove C& R agents being hydrophobic with closed cell structure (moisture resistant) | |
| Hydrophobic | The material should be Hydrophobic | Material dose not absorb any water, chemical or fragrance etc | |
| Leakage proof | The material should be leakage proof | Material, being closed cell structure, is leakage proof & moisture resistant | |
| Unusual Movement Resistance of OT Table: Adhesion of Material | Velcro to be provided for adhesion. | Device is provided with Stick on Surface that can be attached to Velcro to affix device on OT Table preventing unwanted movement of device during Prolonged Surgeries. | |
| | Packaging Mater | ial | |
| Complimentarily of Pack Size, Material, Strength with Item | Suitable packing to withstand transit and accommodate the size of device to be provided | Wooden Box complement to weight of item with size dimensions for ease of fitting with least possible movement during transit | |
| The type of the inner wall of the packing box | The inner walls are laminated coating to prevent any direct contact with absorbent material or if lamination is restricted in region specific regulation on plastic, butter paper is used. | Inner walls of Wooden Box are laminated to prevent any direct contact with absorbent material or otherwise product is wrapped in butter paper if region specific restrictions don't allow use of laminated sheets. | |
| Ultraswachh Disinfection /Sterilization or Gamma Irradiation Sterilization Compatible | Boxes can be sterilized using DRDO's Ultraswachh Sterilization Unit(s) as well as Gamma Irradiation for safety of packaged material for direct utility in OT facility | Gel Technology is compatible for both DRDO's Ultraswachh Sterilization Procedures as well as Gamma Irradiation. User can decide as per available hospital infrastructure. | |
| | Purchase Informa | tion | |
| Warranty in years(For manufacturing defects) | 01 year of comprehensive warranty applicable from Date of Delivery for | Company provides 01 year of comprehensive warranty applicable from | |

| | any manufacturing defects. | Date of Delivery for any manufacturing |
|---------------------------|---|--|
| | | Defects as per T&C applied in |
| | | Manufacturing Warranty Agreement, digitally |
| | | accessible from Signage Information Sticker |
| | | (if available as per option selected). |
| Shelf Life (in years) | Shelf life of item provided should be | Shelf Life of item provided in the lot is ≥ 5 |
| | minimum of 5 years or more. | years applicable from date of manufacturing. |
| Residual Shelf Life (in | Remaining Shelf Life at the time of | As per date of manufacturing, the remaining |
| years) – Not Less than 34 | Supply should be 3/4 th | shelf life of provided item is $\geq 3/4^{\text{th}}$ of |
| of Shelf Life | | applicable Shelf Life of 5 years from Date of |
| | | Manufacturing. |
| Certifications & Reports | Copies of reports and certifications to | All information i.e. certification/ relevant |
| | be furnished to buyer on demand | documentation (reports) in terms of digital |
| | | copy accessible via QR codes labeled on |
| | | packs. Specific confidential certifications are |
| | | provided in physical copies as per requirement furnished by Buyer. It includes |
| | | GST Certification, MSME Registration with |
| | | UAN, Vendor Registration with Government |
| | | Agency (if any), Trademark Registration/ |
| | | Application (as applicable, if any) and other |
| | | Company specific documentation requisite |
| | | for legalized production of items. |
| Web Authentication of | Bath Certification for Supplied Lot | QR Code with digital access to 'batch |
| Material Batch | should be available online for web | certificate' for particular lot Quality Assurance |
| | based authentication by Buyer. | is available outside Item's Pack. |
| | Sites of Application Info | rmation |
| Applications (Health | Operation Theatres, Intensive Care | Item can be deployed in Operation Theatres, |
| Purposes) | Units, X-ray, MRI, Special Wards for | ICUs, X-ray diagnostics, MRI, Eye Clinics, |
| | Comatose/ Semi-Comatose Patients, | Special Wards for both comatose, semi- |
| | Rehabilitation Centres for Elderly, | comatose and regular patients, rehabilitation |
| | Residential Usage for Bed Ridden for | centres for elderly, special children and |
| | Comatose, Semi-Comatose / Non- | persons suffering from specific problems, |
| | Comatose Patients. | effectively useful in household for all types of |
| | | bed-riddent, morbid patients including |
| | | comatose and sem-comatose patients. In |
| | | addition, health parlors with massages and |
| | | physiotherapy clinics as well as reception of |
| | | emergency trauma centers, based on |
| | | functionality of item, it can be used. |